

W5800

BenQ DLP Projector

Features

- True 4K UHD 8.3M Pixel
- 2600lm High Brightness
- BenQ CinematicColor™ 100% DCI-P3 Wide Color Gamut
- HDR10 / HLG / HDR10+
- Factory Calibrated Report
- 1.6X big zoom lens (Motorized)
- Wide-range H&V lens shift (Motorized with rectangular shape)



Product Specifications

Product Number / EAN Code	9H.JSL77.G8E / 471 8755 09297 8
Projection System	DLP
DMD type	0.47"
Native Resolution	4K UHD (3840 x 2160)
Brightness	2600 ANSI Lumens
Contrast Ratio*	2,000,000 : 1 (with Dynamic Black)
Display Color	30 Bits (1.07 billion colors)
Aspect Ratio	Native 16 : 9 (4 ratios selectable)
Light Source	Blue Laser
Light Source life**	Normal 20,000 hrs / Economic 25,000 hrs
Throw Ratio	1.52~2.45
Zoom Ratio	1.6x (Motorized)
Lens	F/# 2.1 ~ 3.0, f 16.0 (Wide) ~25.7 (Tele) mm
Keystone Correction	2D, Manual Vertical & Horizontal ± 35 degree
Lens Shift	Vertical ±50%, Horizontal ±21% (Motorized with rectangular shape)
Projection Size	60" ~ 200" / 300"
Picture Mode	*** ISF Disabled: Bright / Bright Cinema / Cinema / FILMMAKER MODE / 3D / User / HDR10 / HDR10+ / HLG **** ISF Enabled: Bright / Bright Cinema / Cinema / FILMMAKER MODE / ISF Night / ISF Day
DCI-P3 Coverage (Native)	100%
Resolution Support	VGA (640 x 480) to 4K UHD (3840 x 2160)
Horizontal Frequency	15K~135KHz
Vertical Scan Rate	23~240Hz
HDTV Compatibility	720@50P / 60P, 1080@50i / 60i / 24p / 25p / 30p / 50p / 60p / 120P, 2160@24p / 25p / 30p / 60p
Power Consumption (Max / Normal / Eco)	450W / 380W / 240W
Standby Power Consumption	0.5W Max. at 100 ~ 240VAC
Network Stand-by Power Consumption	<2W
Power Supply	VAC 100 ~ 240 (50/60Hz)
Product Dimensions (W x D x H)	525.2 x 392.2 x 145.7 mm
Product Weight	10.5 kg
Noise Level (Normal / Eco)	30dBA / 27dBA
Operating Temperature	0~40 degrees (Celcius)
Special Feature	Motion Enhancer, Local Contrast Enhancer, ISF
Accessories (Standard)	Power Cord (by region, 1.8m) x 1 HDMI Cable (3m) x 1 Remote Control (RCV024:5J.JRX06.001) x 1 Battery (for RC) x 2 Calibration Report x 1 Quick Start Guide x 1 Warranty Card (by region) x 1 Regulatory Statements x 1 User Manual E-edition
Accessories (Optional)	3D Glasses Ceiling mount
On Screen Display Language	English / Traditional Chinese / Simplified Chinese / Hindi / German / French / Italian / Arabic / Indonesian / Thai (10 languages)

* The Contrast is measure by FOFO standard. (Without WCE)
 ** Light life results will vary depending on environmental conditions and usage.
 Actual product's features and specifications are subject to change without notice.
 *** Default picture mode is Bright Cinema
 **** When ISF is enable, default picture mode is ISF Night.

Input and Output Terminals

	I/O Name	Quantity
1	HDMI (HDCP 2.2, TMDs, CEC/ARC/eARC) (Audio Return+) (5.1/7.1 channel audio pass through)	1
2	HDMI (HDCP 2.2)	1
3	USB Type-A (5V/2.0A Media Reader/Firmware upgrade)	1
4	USB Type-A (5V/1.5A Media Reader/Firmware upgrade)	1
5	RJ-45 LAN (Control 4)	1
6	USB Type-B (SERVICE)	1
7	RS232 input (D-sub 9pin, male)	1
8	3D Sync output	1
9	SPDIF audio output (5.1 channel audio pass through)	1




Dimensions



Distance Chart

Screen size				Distance from screen (mm)			Vertical offset (Lowest / Highest lens position)(mm)
Diagonal		H	W	Min length	Average	Max length	
Inch	mm	(mm)	(mm)	(max zoom)		(min zoom)	
60	1524	747	1328	2019	2636	3254	0
80	2032	996	1771	2692	3515	4339	0
95	2413	1183	2103	3197	4174	5152	0
100	2540	1245	2214	3365	4395	5424	0
120	3048	1494	2657	4039	5274	6510	0
150	3810	1868	3321	5048	6592	8136	0
180	4572	2241	3985	6057	7910	9763	0
200	5080	2491	4428	6731	8790	10849	0
250	6380	3113	5535	8413	10987	13561	0
300	7620	3736	6641	10094	13182	16270	0



BenQ Europe B.V.

Meerenakkerweg 1-17
5652 AR Eindhoven
The Netherlands
Tel: +31 88 8889200
Fax: +31 88 8889299

BenQ.eu

© 2024 BenQ Corp. Specification may vary by region, please visit your local stores for details.
Actual product's features and specifications are subject to change without notice.
This material may include corporate names and trademarks of third parties which are the
properties of the third parties respectively.

BenQ